

CLAIMS

1. A joy-dial for providing input signals to a device, said joy-dial having a first and a second x-axis input position, a first and a second y-axis input position, and a first and a second directional input position, a joy pad, an elastically deformable diaphragm located below the joy pad corresponding to each of the x-axis and y-axis inputs, a contact located below and associated with each of the diaphragms and arranged so that pressure applied to the joy pad at one of the x- or a y-axis input positions results in deformation of the corresponding diaphragm and closure of the associated contact, and wherein the joy-dial further includes a first and a second directional contact, said first and second directional contacts being arranged so that they are closed upon movement of the joy-dial in a first or a second direction respectively.

2. A joy-dial according to claim 1 further including at least one diagonal input.

3. A joy-dial according to claim 2 having a diagonal input between each of the first y-axis and the second x-axis input, the second x-axis input and the second y-axis input, the second y-axis input and the first x-axis input and the first x-axis input and the first y-axis input.

4. A joy-dial according to claim 2 wherein pressure applied to a diagonal input position on the joy pad results in deformation of the associated diaphragms of the adjacent x- and y-axis inputs and closure of their associated contacts.

5. A joy-dial according to claim 1 further including a central input.

6. A joy-dial according to claim 5 wherein pressure applied to a central input position on the joy pad results in deformation of each of the diaphragms and closure of their associated contacts.

7. A joy-dial according to claim 1 further including an engagement means which is engaged during rotation of the joy pad and is arranged to push against a biasing means so as to close the associated first and second directional contact.

8. A joy-dial according to claim 7 wherein the biasing means restores the joy pad to a home position in which none of the contacts are closed once pressure applied by the user is removed.

9. A joy-dial according to claim 1 wherein movement of the joy-dial in the first or the second direction is achieved by respective clockwise and anti-clockwise rotation of the joy pad.

10. A joy-dial according to claim 1 wherein the joy pad can be rotated substantially 45° in either a clockwise or anti-clockwise direction about a z-axis.

11. A joy-dial according to claim 1 further including a base arranged for attachment to an information device or to a printed circuit board of a device and a cage means arranged to be connected to said base and to locate the joy pad there between.

12. A joy-dial according to claim 11 wherein a biasing means is located between the joy pad and an upper surface of the base.

13. A joy-dial according to claim 1 wherein the joy pad is marked to indicate the positioning of the input positions.

1 14. A joy-dial according to claim 1 wherein the joy pad has an upper surface
2 which is patterned to enhance grip to the joy pad by the user's finger.

3
4 15. A joy-dial according to claim 1 wherein the joy pad is mounted for pivotal
5 movement on a pivot means.

6
7 16. A joy-dial according to claim 15 wherein the joy pad includes an
8 engaging member on an underside, said engaging member being arranged to
9 engage within a groove formed in an upper surface of said pivot means.

10
11 17. A joy-dial according to claim 16 wherein the engaging member is located
12 in a hollow or aperture formed in the underside of the joy pad.

13
14 18. A joy-dial according to claim 16 wherein the groove is annular so as to
15 enable the joy pad to turn in a clockwise or anticlockwise direction.

16
17 19. A joy-dial according to claim 1 wherein the joy pad includes at least one
18 thumb rail arranged to aid the user to rotate the joy pad.

19
20 20. An information device having at least one joy-dial, said joy-dial being
21 arranged to provide input signals to the device, said joy-dial having a first and a
22 second x-axis input position, a first and a second y-axis input position, and a
23 first and a second directional input position, a joy pad, an elastically deformable
24 diaphragm located below the joy pad corresponding to each of the x-axis and y-
25 axis inputs, a contact located below and associated with each of the
26 diaphragms and arranged so that pressure applied to the joy pad at one of the
27 x- or a y-axis input positions results in deformation of the corresponding
28 diaphragm and closure of the associated contact, and wherein the joy-dial
29 further includes a first and a second directional contact, said first and second
30 directional contacts being arranged so that they are closed upon movement of
31 the joy-dial in a first or a second direction respectively.

1 21. A device according to claim 20 further including a microprocessor or the
2 like which is arranged to detect closure of any of the contacts and to interpret
3 such as a logical state change.

4

5 22. A device according to claim 20 further including an operating system
6 which is arranged to be informed by the micro processor of a logical state
7 change and to in turn inform a software application which interprets the
8 information for executing a corresponding or an associated action

099291.0601
T09290"21E26860